

# terreno™

COLORBODY™ PORCELAIN TILE





Photo features Terreno 6 x 24 in Smokewood in a random staggered pattern.  
Cover photo features Terreno 6 x 24 in Smokewood in a random staggered pattern.

# terreno

Exotic, golden Teak makes its way to a corner bistro. Redwood's deep cherry hue finds its place in an urban loft. Terreno realistically parlays the character of wood, embodied in a sleek porcelain tile.



# see the forest for the tile

With its sleek and modern lines, Terreno Colorbody™ porcelain artfully embodies the rich aesthetic of hardwood flooring – ideal for spaces where wood just isn't an option. With solid color throughout the tile, Terreno makes short work of challenges like high traffic volume or excess humidity.

Whether starkly contemporary or staidly classic, Terreno stakes its claim to any and all surroundings. Nature-inspired hues like Smokewood and Black Forest elevate and decor. A clean, linear graphic with traditional wood signatures never fail to create an atmosphere of stylish sophistication.



colors





# branch out

Let the possibilities stretch your imagination. Terreno is available in a 6 x 24 plank size to replicate hardwood flooring, while offering the durability and convenience of porcelain. Its six color options, easily accommodate any color scheme.

From hall to hearth, from dining to dreaming, Terreno radiates warmth and vivacity. This versatile option is ideal for commercial and residential spaces and can be placed randomly or in a distinctive grid.

With durability to spare, the Terreno Colorbody™ porcelain collection is ready for its close-up. Whether capturing the gaze of passing patrons or esteemed guests, Terreno stands out in the crowd.

Photo features Terreno 6 x 24 in Smokewood on the floor in a random staggered pattern.



# FIELD TILE

---



Driftwood TE15



Teak TE16



Sandalwood TE17



Smokewood TE19



Redwood TE18



Black Forest TE20





SIZES, SHADE VARIATION & PRICING

---



**6 x 24 Field Tile**  
(5 7/8" x 23 5/8")  
(15 cm x 60 cm)



**Medium**  
(V2)

Tile Thickness: 3/8"  
Recommended Grout Joint: 3/16"  
Pricing: High

TRIM

---



**Bullnose**  
S43F9  
3 x 24



Photo features Terreno in Redwood 6 x 24 shown in a random staggered pattern.

## PERFORMANCE CHARACTERISTICS

C.O.F.		Moisture Absorption	Breaking Strength	MOH's	Abrasion Resistance	Chemical Resistance
Wet	Dry					
≥0.60	≥0.70	<0.5%	>400 lbs.	8.0	N/A	Resistant

## APPLICATION

RES	LT COM	HVY COM	COM EXT	
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	Floors †
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	Walls/Backsplashes
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	Countertops
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	Pool Decking
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	Pool Lining

### APPLICATION NOTES:

† Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection.

Not for use on ramps.

Suitable for exterior walls in freezing and non-freezing climates when proper installation methods are followed.

For additional information, refer to Factors to Consider at [www.americanolean.com/CommercialFactors](http://www.americanolean.com/CommercialFactors).

- Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface.
- Use of a latex modified thin-set is recommended for proper installation.

### Cleaning Procedures

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for porcelain tile
- Remove cleaning solution with a clean, damp sponge or mop

### Installation Methods

#### Backing Materials

- Concrete
- Mortar bed
- Cementitious backer board

#### Setting

- Latex modified thin-set
- Epoxy

#### Grouting

- Sanded grout
- Sanded cement grout
- Epoxy grout
- Recommended grout joint: 3/16"

## NOTES

Since there is shade variation in all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.



American Olean Greenworks is part of the Mohawk Greenworks™ corporate initiative. Visit [mohawkgreenworks.com](http://mohawkgreenworks.com) for more details.



captivate

americanolean.com



888-AOT-TILE

© 2010 American Olean CSAOTERRENO