

METROPOLITAN QUARRY

BY FLORIDA TILE


Indoor/Outdoor



Natural, high density, all-weather performance. Florida Tile Quarry has the distinction of being an unglazed ceramic tile, made in the United States, which can be installed inside or out, is frostproof and maintains high-quality style, and durability. Color throughout the body of the tile supports wearability. Wearing, over time, actually produces a natural patina and deeper character. Where performance and style is required, Florida Tile Quarry is the right choice.

Note: Florida Tile recommends a penetrating sealant according to use and care sheet available from your distributor. Never use a surface type coating sealer because they do not adhere well to the tight die-skin surface.


In Stock Size Availability:



QUARRYBASICS® CLEAR TONES



77310 Mayflower Red




77507 Puritan Gray


TYPICAL PROPERTIES

Specification	Test	Result
Absorption	ASTM C373	3% Maximum
5-Hour Boil		Qualifies as Vitreous
Compression Strength	ASTM C67	Min. 10,000 P.S.I.
Freeze/Thaw	ASTM C67	15 Cycles
	Special Florida Tile Freeze/Thaw Test	Min. 3,000 Cycles
Abrasion Resistance	ASTM C501	Index of 35 or Better
Breaking Strength	ASTM C648	400 lbs. or Better
Shear-Bond Strength	ASTM C482	50 P.S.I or Greater
Static C.O.F.	ASTM C1028	At time of manufacture, exceeds measure of 0.5. Internal testing shows results of 0.6 and higher.
Facial Size Variation	ASTM C499	Average facial dimension of each tile not to exceed 4% from nominal dimension(s). No industry standard.
Wedging	ASTM C502	Max. 1.0%
Warpage	ASTM C485	Max. 1.5% Along Any Edge 1.0% on either diagonal.
Thickness	ASTM 499	Max. Range of .050

QUARRYBASICS® X-COLORS



7731X Commercial Red
Available in 6x6 and 8x8 only



7757X Stone Gray

X-Colors available in trim sizes Q1665 and Q1665C only.

METROTREAD®



7731T Red
6x6 only




7757T Gray
6x6 only


Added Slip Resistance

METROTREAD® features nine raised treads across the surface of each tile, spaced 5/8" apart for added slip resistance.

Please Note: METROTREAD® is a floor layout program and should only be used in one of two patterns depending on the application.



Grid System - for use in multidirectional traffic such as commercial kitchens.



Linear System - for use in one directional traffic such as access ramps and directional pathways.

COLOR VARIATIONS

Variations in shade, color and texture is an inherent characteristic of all fired clay tiles. Variations may occur from one product run to another. All colors shown are accurate as printed applications can be. Selection should be made from actual samples. Blend tile from several cartons for best shading

FLORIDA TILE LIMITED WARRANTY

Florida Tile warrants that our products will meet the testing standards and specifications set forth in our current product literature. In the event of a defect Florida Tile will replace the defective tile F.O.B. plant if timely notice of the defect is received by the dealer from whom the tile was purchased prior to installation of the tile. Because specific installation details, structural design and environmental conditions are beyond Florida Tile's control, we are not responsible for performance of our tiles once they are installed.

Quarry Tile Trim Pieces

This grouping available in 77310 and 77507 only

This grouping available in 77310, 77507, 7731X and 7757X



FLORIDA TILE, INC. • LAKELAND, FLORIDA 33802

1-800-FLA-TILE

http://www.floridatile.com/