

MARAZZI  USA

the fine art of porcelain stoneware

Made In The USA



(riflessi di legno)

color body porcelain stoneware | rectified



ash

4"x24" Rectified - 6"x24" Rectified - 12"x24" Rectified

(riflessi di legno)



cherry

4"x24" Rectified

RIFLESSI DI LEGNO repurposes conventional wood graining into the economical, easily maintained medium of color body porcelain tile. Boldly rustic, boldly sized, boldly colored, it's poised to dramatically influence any environment.



Distinctive graining in five authentic hardwood colors fits right into commercial or residential areas where ADA-compliant slip-resistance is important. The series is chameleon-like in that it is equally at ease in the casual, relaxed settings of a weekend retreat, as the sophisticated backdrop for a retail or hospitality venue, in trendy lofts with an urban chic bent.

Rectified sides permit precise alignment with small grout joints, making it a viable option for walls as well as floors, indoors and out.



ebony

4"x24" Rectified - 6"x24" Rectified - 12"x24" Rectified



oak

Floor: 6"x24" Rectified Wall: Crystal Stone Caramel



walnut

4"x24" Rectified - 6"x24" Rectified

(riflessi di legno)



UJ3J Ash
12"x24"
Rectified



UHAJ Ash
6"x24"
Rectified



UJ3P Ash
4"x24"
Rectified



UJ3K Cherry
12"x24"
Rectified



UHAK Cherry
6"x24"
Rectified



UJ3Q Cherry
4"x24"
Rectified



UJ3L Ebony
12"x24"
Rectified



UHAL Ebony
6"x24"
Rectified



UJ3R Ebony
4"x24"
Rectified

technical

ASTM Test Results

Technical Characteristics	ASTM Standards	ASTM Test Results	ASTM Test Methods
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS Scale
Breaking Strength	≥ 250 lbf.	≥ 583 lbf.	C648
Facial Dimension	-3.0% < Nominal ≤ 2.0%	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (squareness)	+/- 0.25% or +/- 0.8 mm**	Within Standard	C502
Warpage (flatness)	+/- 0.40% or +/- 1.8 mm**	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV*	C1027
Dry Coefficient of Friction	As Reported	0.80 ≤ C.O.F. < 0.90	C1028
Wet Coefficient of Friction	As Reported	0.60 ≤ C.O.F. < 0.70	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Abrasion Resistance / Suggested Applications
Class IV: Tile in this class may withstand heavier amounts of traffic with greater amounts of dirt and/or other abrasives present, including commercial kitchens, and areas with regular traffic from the outside. See Coefficient of Friction and Frost Resistance for installation-specific details.

** Whichever is less



Floor Tile



Wall Tile



Modular Tile



Rectified Tile



Suitable for Outdoors



Slight Variation



Frost Resistant



Meets ADA Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



21% Minimum Pre-Consumer Recycled Content



Certified No VOC



Contributes to LEED Credits



UJ3M Oak
12"x24"
Rectified



UHAM Oak
6"x24"
Rectified



UJ3S Oak
4"x24"
Rectified



UJ3N Walnut
12"x24"
Rectified



UJ3H Walnut
6"x24"
Rectified




UJ3T Walnut
4"x24"
Rectified


Decorative Options



LG4B Caramel
12"x12"

packaging

	Sizes	Pcs	Sq. Ft.	Weight (lbs.)	Thickness
Modular Tile	4"x24" R	15	9.32	55	0.433
Modular Tile	6"x24" R	10	9.46	51	0.433
Modular Tile	12"x24" R	5	9.51	55	0.433
Crystal Stone	12"x12"	12	11.63	42	Compatible

	Sizes	Ctn	Sq. Ft.	Weight (lbs.)
Modular Tile	4"x24" R	40	372.80	2200
Modular Tile	6"x24" R	40	378.40	2084
Modular Tile	12"x24" R	40	380.40	2200



American Marazzi Tile, Inc.
Headquarters & Manufacturing Plant

359 Clay Road
Sunnyvale, Texas 75182

T 972.226.0110
F 972.226.5629
www.marazzitile.com
contact@marazzitile.com



Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with American Marazzi Tile Customer Service for details.